

MANUFACTURE

Flashing and Frame

STANDARD MATERIALS

 $0.75 mm \ Zincalume \ B$ steel spot welded for superior strength.

STANDARD FINISH

Mill

Powder coated to match Colerbond

....

Glass
STANDARD COLOUR

colour range.

STANDARD MATERIALS

Clear

10.38mm laminated safety glass.

DIFFUSER TYPES

Concave Diffuser

Available in both Prismat® & WarmGlo®

Flat Diffus

Available in both Prismat® & WarmGlo®



Prismat®

The standard diffuser is a Clear Prismatic Diffuser that eliminates glare and produces an even spread of light by the female conical prism refracting properties.



WarmGlo®

The option diffuser is available in both flat and convex shape. The WarmGlo Diffuser is a frosted white translucent diffuser that eliminates glare and produces a bright light that is softened for visual comfort.

RATINGS



U-Value 0.98 SHGC 0.85

.90 S .85 V

SHGC 0.85 VLT 98%



Complies with Bushfire AS 3959-2009

* Rating based on installations above 18°. Refer to Ember Guard.



EMBER GUARD

An extra level of protection on roofs pitched below 18° and to meet BAL-29 requirements. The Skyspan Bushfire Ember Guard is manufactured from black stainless steel flyscreen mesh.

TYPICAL INSTALLATION

Roof Pitch Range: 0°-45

Shaft





Diffuser

Ceiling Trim



FURTHER ONLINE INFORMATION

INSTALLATION INSTRUCTIONS skyspan.com.au/installation
TECHNICAL DRAWINGS skyspan.com.au/drawings
PRICES skyspan.com.au/traditional-skylight



1300 SKYSPAN (759 772)

sales@skyspan.com.au skyspan.com.au







